



Learn more here

			INTERIOR				
	Heyers WOODCARE DEXPRESS WITH THE PROPERTY OF THE PROPERTY O	WOODCARE WEXTERNSH THE REPORT OF THE PROPERTY OF THE PROPERT	WOODCARE WEX PRIMER I I	Household WOOD CARE DECKING OIL MARKET OF THE CONTROL OF THE CON	Hayands WOODCARE EXTERIOR VARNISH ORANGE O	WOODCARE WOODSTAIN	WOOD CARE INTERIOR VARNISH
	Dexpress Deck & Timber Stain	UVEX Finish	UVEX Primer	Decking Oil	Exterior Varnish	Wood Stain	Interior Varnish
Finish	Low Sheen	Satin	Undercoat	Matt	Gloss		Gloss & Satin
Product Code	WED	WEU	WEUP	WEDO	WEV	WIWS	WIVG & WIVS
Size	1L, 2L, 4L, 10L	1L, 4L, 10L	1L, 4L, 10L	1L, 4L, 10L	500mL, 1L, 4L	250mL, 500mL, 1L	250mL, 500mL, 1L, 4L
Application Tools	Deck BrushLambswool applicator	Deck BrushLambswool applicator	Deck BrushLambswool applicator	· Lambswool applicator	Mohair roller short nap		Mohair roller
Clean-up	Water	Water	Water	Mineral Turpentine	Mineral Turpentine	Mineral Turpentine	Mineral Turpentine
Recoat (at 25°C & 50% humidity)	2 hours	2 hours	3 hours	6 hours	16 hours	24 hours	8 hours
Coverage	Up to 12 sqm/L dependent upon surface porosity, profile and method of application.	Up to 12 sqm/L dependent upon surface porosity, profile and method of application.	Up to 10sqm/L dependent upon surface porosity, profile and method of application.	Up to 10 sqm/L dependent upon surface porosity, profile and method of application.	Up to 12 sqm/L dependent upon surface porosity, profile and method of application.	Up to 12sqm/L dependent upon surface porosity, profile and method of application.	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.
Preparation	Woodcare Exterior Wood Cleaner & Woodcare Rapid Prep	Woodcare Exterior Wood Cleaner & Woodcare Rapid Prep	Woodcare Exterior Wood Cleaner & Woodcare Rapid Prep	Woodcare Exterior Wood Cleaner & Woodcare Rapid Prep	Woodcare Exterior Wood Cleaner & Woodcare Rapid Prep	Refer to Product Data Sheet	Refer to Product Data Sheet
Interior	No	No	No	No	Yes	Yes	Yes
Exterior	Yes	Yes	Yes	Yes	Yes	No	No
Features & Benefits	 Hard-wearing Ideal for high traffic areas Quick-drying Get the job done faster, you can apply 2 coats in one day. Long-lasting protection Protects against wear and tear and UV damage for longer 	 Highlights timber's natural appearance Attractive satin finish Outstanding durability Long lasting, less maintenance Formulated for Australian conditions High UV resistance, protects for longer 	Stabilising pre-treatment Protects timber during the construction period Primes and penetrates Improves longevity of the UVEX Finish	 Will not crack or peel Weathers naturally Penetrates and preserves Nourishes timber to guard against cracking and splitting Mould and algae resistant To protect the timber from early deterioration 	 Oil-enriched Enhances timber's natural beauty Hard-wearing gloss finish Helps to repel dirt and contaminants UV Protection Long - lasting performance 	 Enhances timber grain Adds colour to transform your timber Simple to apply Achieve a professional result Ready for use Apply directly to the timber 	 Long-lasting Protects surfaces against wear and tear for longer Easy to clean Low maintenance Hard-wearing Tough durable finish



	INTE	RIOR	INTERIOR FLOORING							
	Hay Wood			WOODCARE EASY FLOOR TO SEE SEE SEE SEE SEE SEE SEE SEE SEE SE		WOODCARE AQUALAC FLOOR THE CONTROL OF THE CONTROL		WOODCARE TUNG OIL FINISH		
	Aquala	ic Clear		Easy Floor		Aqualac Floor		Tung Oil Finish		
Finish	Satin	Gloss	Gloss	Satin	Satin Non-Slip	Gloss & Satin	Satin Non-Slip	Satin		
Product Code	WIACS	WIACG	WIEFG	WIEFS	WIEFSNS	WIAFG & WIAFS	WIAFSNS	WITOF		
Size	500mL, 1L, 4L	500mL, 1L, 4L	1L, 4L, 10L	1L, 4L, 10L	1L, 4L	1L, 4L, 10L	1L, 4L	1L, 4L, 10L		
Application Tools	Airless sprayMohair roller short napSynthetic brush	Airless sprayMohair roller short nap	Lambswool applicatorMohair roller	Lambswool applicatorMohair roller	Lambswool applicatorMohair roller	Lambswool applicatorMohair roller	Lambswool applicatorMohair roller	Lambswool applicatorMohair roller		
Clean-up	Water	Water	Mineral Turpentine	Mineral Turpentine	Mineral Turpentine	Water	Water	Mineral Turpentine		
Recoat (at 25°C & 50% humidity)	3 hours	3 hours	16 hours	16 hours	16 hours	3 hours	3 hours	16 hours		
Coverage	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.	Up to 14 sqm/L dependent upon surface porosity, profile and method of application.	Up to 14 sqm/L dependent upon surface porosity, profile and method of application.	Up to 14 sqm/L dependent upon surface porosity, profile and method of application.		
Preparation	Refer to Product Data Sheet	Refer to Product Data Sheet	Refer to Product Data Sheet	Refer to Product Data Sheet	Refer to Product Data Sheet	Refer to Product Data Sheet	Refer to Product Data Sheet	Refer to Product Data Sheet		
Interior	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Exterior	No	No	No	No	No	No	No	No		
Features & Benefits	 Quick-drying Get the job done faster, you can apply 2 coats in one day. Harding-wearing Tough durable finish Non-yellowing Perfect for light coloured timbers 	 Non-yellowing Perfect for light coloured timbers Harding-wearing Tough durable finish Quick-drying Get the job done faster, you can apply 2 coats in one day. 	 Enhances and protects Highlights natural beauty of timber Easy to clean Low maintenance Hard-wearing Ideal for high traffic areas 	Easy to clean Low maintenance Enhances and protects Highlights natural beauty of timber Hard-wearing Ideal for high traffic areas	 Pre-mixed Easy to use Final coat application Certified slip rating 	 Durable finish Scratch & mark resistant Low-odour No fumes or lingering odour Quick-drying Get the job done faster, you can apply 2 coats in one day. 	 Final coat application Certified slip rating Pre-mixed Easy to use 	 Anti Chip Will not crack or chip Easy to maintain Simple re-application process Satin lustre finish Perfect for hiding marks and dust 		